

Declaration of Performance

EC Construction Products Regulation
EN 12326 Roofing & Cladding Slate



PRIMERA
FINEST NATURAL SLATE

86 Ramsey Road
Warboys
Huntingdon
Cambridgeshire
PE28 2RW
Tel: +44 (0)1487 825 222
Fax: +44 (0)1487 825 240
info@primeraslate.co.uk
www.primeraslate.co.uk

DOP Number:		DOP 19/008		
1. Unique identification code of the product-type:		Capimor		
2. Type, batch or serial number or any other element allowing identification of the construction product:		50x25 60X30		
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:		Slate for discontinuous roofing and cladding		
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:		Pizarras Del Valle S.L. A Medua S/N 32330 Carballeda De Valdeorras, Ourense		
5. Where applicable, name and contact address of the authorised representative:		N/A		
6. System or systems of assessment and verification of consistency of performance of the construction product:		System 4		
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:		The manufacturer has carried out factory production control and determination of product type based upon System 4 within the Assessment of Conformity Tasks.		
8. In case of the declaration of performance concerning a construction product covered by a European Technical Assessment:		N/A		
9. Declared Performance:				
Essential Characteristic for Pitched Roof Coverings:	Performance:		Harmonized Technical Specification:	
Mechanical Resistance:	Mean Failure Load:		EN12326-2:2011	
	Transverse: 902.5N	Longitudinal: 1041.4 N		
	Characteristic MOR:			
	Transverse: 59.4 Mpa	Longitudinal: 69.8 Mpa		
External Fire Performance:	Deemed to satisfy		EC Decision 2000/553/EC	
Reaction to Fire:	Deemed to satisfy Class A1		EC Decision 96/603/EC as amended	
Dimensional Variation:			EN12326-2:2011	
Slate Type:	Very Smooth	Smooth	Normal	Textured
Deviation from flatness:		<1.0%		
Nominal thickness and variation:		5mm +/- 35%		
Deviation from declared width:	+/- 5mm			
Deviation from declared length:	+/- 5mm			
Deviation from straightness of edges:	+/- 5 mm			
Deviation from rectangularity:	+/- 1%			
Durability:			EN12326-2:2011	
Water absorption:	Code A1 0.36%			
Freeze thaw:	Not Required			
Thermal cycle test:	Code T1			
Carbonate content:	0.5%			
Sulphur dioxide exposure tests:	Code S1			
Non-carbonate carbon content:	0.5%			
Release of dangerous substances:	None in conditions of use as roofing or external cladding		EN12326-2:2011	
10. Declaration: The product(s) identified in Points 1 and 2 is in conformity with the declared performance under point 9. This declaration of performance is the sole responsibility of the manufacturer identified in point 4.				
Place & Date of Issue: PRIMERA SLATE COMPANY LIMITED 86 Ramsey Road, Warboys, Huntingdon, Cams PE28 2RW 1 st May 2019		Name: Mr Stephen Harding Position: Managing Director Signature: 		